

BOOT DRYER FORCE



STANDARD



100%

↓ TECHNOLOGY

OPENING NOZZLE SYSTEM

Increased efficiency & energy-saving

TOUCHSCREEN

Communication between the user & the device

ELECTRONIC CONTROL

Optimisation & operational efficiency

DRYING EFFICIENCY

Carefully designed systems & selected components

DISINFECTION SYSTEM

Two proven methods for disinfecting equipment

PROTECTION SYSTEM

Safety of use

RUNNING SYSTEM

Space saving, mobile & convenient

FRAME

Rigid structure, safety of use

DOUBLE PROTECTION

Durability & protection against corrosion

FOUR VISUAL LINES

Diverse design of the front panel



↓ DETAILS



MINIPANEL



PANEL



UNIQ



↓ STORAGE CAPACITIES

Length	Capacity*	Width	Height	Power** W	Voltage** V
1500	48	800	2250	260/5680	230/3x400
1800	60	800	2250	260/5680	230/3x400
2000	72	800	2250	510/7730	230/3x400
2400	84	800	2250	510/7730	230/3x400
3000	108	800	2250	510/7730	230/3x400
4000	144	800	2250	2x510/7730	230/3x400

* Pairs of boots | ** Without / with heating | Dimensions MM