

BOOT DRYER OPTIFLOW

 100%

- > **Four product lines**
Different design variants
- > **The frame**
Rigidity and confidence
- > **Touchscreen**
Pure convenience and user-friendliness
- > **Galvanized steel and powder coating**
Double protection
- > **Mobile racking system**
Easy and smooth movement
- > **Electronic control**
Energy efficiency and convenient control
- > **Extreme drying performance**
Selected powerful drying components
- > **Tubes with open-close nozzles**
Increased drying efficiency and energy saving
- > **Disinfection system**
Proven and complex germicidal solution
- > **Reliable electrical protection**
Safety of use

Technology



Details



Storage capacities

| Length | > | Capacity | Power | Voltage | Width | Height |
|--------|---|----------|-------------|----------|-------|--------|
| 1500 | > | 44 | 550/7150 | 3x400 | 500 | 2420 |
| 1800 | > | 55 | 550/7150 | 3x400 | 500 | 2420 |
| 2000 | > | 66 | 550/7150 | 3x400 | 500 | 2420 |
| 2400 | > | 77 | 550/7150 | 3x400 | 500 | 2420 |
| 3000 | > | 99 | 550/7150 | 3x400 | 500 | 2420 |
| 4000 | > | 132 | 2x 550/7150 | 2x 3x400 | 500 | 2420 |

mm > pairs of boots; W (heating off/on); V